



extriCARE® 3600

Negative Pressure Wound Therapy System

Distributor Sell Sheet



extriCARE® 3600

Negative Pressure Wound Therapy System

The ExtriCARE® 3600 NPWT System is designed to optimize wound healing by effectively removing wound exudates, infectious material, and tissue debris from the wound bed. It administers continuous or intermittent negative pressure to suit individual patient needs. This powerful yet user-friendly device is ideal for various healthcare settings.

Enhancing Wound Care with ExtriCARE®

The ExtriCARE® 3600 utilizes advanced Hybrid hNPWT technology, allowing the use of both traditional foam dressing kits and anatomically fitted bandage dressings. This versatility promotes effective wound healing by providing tailored solutions for various wound types.

Features and Benefits:

- **Easy to Use:** Our intuitive design and user-friendly interface simplify operation, making it accessible for healthcare professionals and caregivers alike.
- **Versatile:** Equipped with a high-capacity, high-flow pump, the ExtriCARE® 3600 ensures comprehensive care for a wide range of wound types.
- **Powerful:** The long-lasting rechargeable battery supports up to 24 hours of continuous treatment, providing reliable performance when needed most.

Order Information

Product Descriptions	Packaging
extriCARE 3600 NPWT unit	4 units per shipper
400cc Canister for extriCARE 3600 unit	20 pieces per shipper
1000cc Canister for extriCARE 3600 unit	20 pieces per shipper
Carrying case for EC3600 unit utilizing 400cc canister	50 pieces per shipper
Carrying case for EC3600 unit utilizing 1000cc canister	50 pieces per shipper
Charger for extriCARE 3600 unit	20 pieces per shipper
Bed/Pole clamp for extriCARE 3600 unit	20 pieces per shipper
	extriCARE 3600 NPWT unit 400cc Canister for extriCARE 3600 unit 1000cc Canister for extriCARE 3600 unit Carrying case for EC3600 unit utilizing 400cc canister Carrying case for EC3600 unit utilizing 1000cc canister Charger for extriCARE 3600 unit

Device Specficications

Product Code:	EC3600 (MI390)
Weight:	2.87 lbs (1.3kg)
Battery Type:	Lithium (rechargeable)
Vacuum Modes:	Continuous or intermittent
Pressure Range:	40-200 mmHg
Charge Time:	< 5 hours
Canister size:	400cc and 1000cc
Dimensions:	Length: 6.7" (17cm) Height: 5.1" (13cm) Depth: 4.3" (11cm)
Input:	100-240 V 50/60 Hz 1.5 A



Alleva Medical Ltd

Suite M-Q, 12th Floor, Kings Wing Plaza 2, 1 On Kwan Street, Shatin, Hong Kong Tel: +852 3166 7200 www.allevamedical.com

Distributed in the USA exclusively by ExtricareUSA LLC

Suite 205, 2460 General Armistead Avenue, Norristown, PA 19403 Tel: 877-312-NPWT info@extricareusa.com

All products are manufactured under US FDA, ISO 13485, and Japan PMDA registered facility of Alleva Medical Ltd.







vextricareusa com www.allevamedica